

SP AIR CORPORATION PNEUMATIC TOOLS FOR PROFESSIONAL 2014~2015 CATALOG MADE IN JAPAN ••



WARNING

This must be read and understood by operating personal and safety manager.

Protection to operating personal, as well as adjacent areas, shall be maintained and inspected tools in accordance with any applicable safety codes and regulations at all the times.

Stop using tools when tool produces unusual sound, repair immediately.



ISO9001



A complete range of high quality automotive, industrial and general service pneumatic tools manufactured in Japan for professionals.

Specifications subject to change without notice.

Performance figures are at 90 psi pressure with 3/8"ID 2m long air hose.

IMPACT WRENCH:

Torque figures developed on Skidmore-Wilhelm torque-tension tester at 90psi air pressure.

Working torque figures are after 5 seconds of impacting.

Maximum torque figures are after 15 seconds impacting.



SP AIR tools satisfy the requirements of EC Machine Directive (2006/42/EC).

- Measurements according to ISO-2787.
- · Noise levels according to ISO-15744.
- · Vibration levels according to ISO-8662.

Contents

ooments .	
Model No.	Page
SP-1133, SP-1133-2	14
SP-1140EX	5
SP-1148TR-X	5
SP-1158. SP-1158L	7
SP-1158EX, SP-1158EXL	7
SP-1175B, SP-1176B	12
SP-1186GE. SP-1186GE-8	10
SP-1190A-2, SP-1190A-6, SP-1190A-8	9
SP-1190EXA-2, SP-1190EXA-6, SP-1190EXA-8	9
	9
SP-1190EXPA-2, SP-1190EXPA-6	9
SP-1190PA-2, SP-1190PA-6	
SP-1191DH, SP-1191LDH	8
SP-1191EXDH, SP-1191EXLDH	0/07
SP-1192EX-2, SP-1192EX-6, SP-1192EX-8	10
SP-1193GE-8, SP-1193GEP-2, SP-1193GEP-6	25
SP-1220S	16
SP-1251LABV	19
SP-1254	16
SP-1257	16
SP-1261L14	16
SP-1350	20
SP-1370A	20
SP-1380	20
SP-1410, SP-1410H, SP-1410K	22
SP-1460	24
SP-1460FC	24
SP-1470	24
SP-1470FC	24
SP-1490L	23
SP-1510AH-KL	18
SP-1522KL	18
SP-1523KL	18
SP-1523S	16
SP-1525KL	18
SP-1527KL	18
SP-1533KL	18
SP-1760A, SP-1762	14
SP-1764, SP-1765	11
SP-1800, SP-1800A	21
SP-1810, SP-1810A	21
SP-1850, SP-1850H	5
SP-3606-A5, SP-3606DF-A5	20
SP-5000GE	10
SP-6500	10
SP-7130, SP-7131	14
SP-7130RH, SP-7131RH	13
SP-7140	6
SP-7141	6
SP-7142DX, SP-7142DXS	6
SP-7143DX	6

Model No.	Page
SP-7144	3
SP-7145	4
SP-7146	5
SP-7150	7
SP-7151	7
SP-7191, SP-7191S	8
SP-7200	16
SP-7201	16
SP-7201G	20
SP-7202	16
SP-7211	15
SP-7220	15
SP-7230	15
SP-7240H	15
SP-7241GH	20
SP-7241H	15
SP-7500AH-P	20
SP-7520KL	17
SP-7525KL	18
SP-7527KL	18
SP-7600	22
SP-7720A, SP-7722A	11
SP-7730, SP-7731	12
SP-7740RH, SP-7742RH	13
SP-7760, SP-7762	14
SP-7770, SP-7772	13
SP-7810, SP-7810A	22
SP-7825	5
SP-7825HU	21
SP-8102BU	21

Category	3P1925
IMPACT WRENCHES	13~14
RATCHET WRENCHES	11~12
REACTION FREE RATCHET WRENCH	15~16
DIE GRINDERS	17~18
DRILLS	20
SANDER / POLISHER	21~22
DRIVERS	16
DISC GRINDERS	22
SAW / HAMMER	23~24
NEEDLE SCALERS / FLUX CHIPPERS	19
BEVELER	26
ANVIL KITS / AIR SUPPLY	

LIMITED WARRANTY .

We guarantee all of our products against defective workmanship and faulty materials for 6 months from the date of purchase. We undertake, in accordance with our own option, to replace or repair free of charge each product or part thereof on condition

We undertake, in accordance with our own option, to replace or repair free of charge each product or part thereof on condition that the machine or parts in question is:
returned to us or one of our authorized distributors, freight pre-paid.
found, on examination, to be suffering from a material or constructional defect.

This warranty does not cover damage to any unit caused by accident, misuse, claims arising from loss, fire or other calamities caused by nature, or in any way being tampered with.

The warranty does not cover damage resulting from:
1) Installation to wrong air pressure.
2) Any alteration or modification to the to tool and or its serial number.
3) Any unauthorized repair carried out

- 3) Any unauthorized repair carried out.
- 4) Any damage caused by the life.



SP-7144 1/2" COMPOSITE IMPACT WRENCH



Model Size Short! 1-3/16" shorter than SP-7140.

SQ.DRIVE 1/2" 5/8" **BOLT CAPACITY** MAX TORQUE (F) 750 ft-lbs. (R) 800 ft-lbs. FREE SPEED : (F) 5,700 rpm (R) 6,500 rpm **OVERALL LENGTH** 6-1/16" WEIGHT 4 lbs. VIBRATION LEVEL 5.5 m/s² 93.1 dB SOUND LEVEL AIR INLET 1/4"NPT

SP-7145 1/2" COMPOSITE IMPACT WRENCH





SPECIFICATIONS

SQ.DRIVE : 1/2" **BOLT CAPACITY** : 5/8"

MAX TORQUE : (F) 750 ft-lbs.

(R) 800 ft-lbs.

FREE SPEED : (F) 5,700 rpm

(R) 6,200 rpm

OVERALL LENGTH : 6-1/2" : 4.2 lbs.

WEIGHT

VIBRATION LEVEL : 6.0 m/s² SOUND LEVEL : 91.5 dB

AIR INLET

: 1/4"NPT

'SOLDR. IMPACT WRENCH & IMPACT DRIVER



Butterfly throttle for single-handed control of speed and forward or reverse



Sq.Drive **Bolt Capacity** 3/8" Max. Torque Range : 72 ft-lbs. Free Speed Overall Length Net Weight

10,000 rpm : 5-3/8" : 1 lbs. Vibration Level : 6.2 m/s Sound Level : 87.4 dB

SP-7825 (3/8")

Lightweight Composite Body



Sq.Drive **Bolt Capacity** Max. Torque Range Free Speed Overall Length : 1.5 lbs.

Net Weight Vibration Level Sound Level



One Hand **Reverse Button**



DR. IMPACT WRENCHES

SP-1140EX (1/2")



Sq.Drive **Bolt Capacity** Max. Torque Range Free Speed Overall Length Net Weight Vibration Level Sound Level

: 1/2" 5/8" : 800 ft-lbs. 6,000 rpm 7-1/4" : 5.7 lbs. : 3.4 m/s : 88.8 dB



SP-1148TR-X (1/2")

: 3/8"

: 4 m/s2

: 84.2 dB



Sq.Drive : 1/2" **Bolt Capacity** : 5/8" : 650 ft-lbs. : 6,300 rpm Max. Torque Range Free Speed 7-3/4" Overall Length Net Weight : 6 lbs. Vibration Level : 3.16 m/s² : 91 dB Sound Level



SP-7146 (1/2") **mini**





Sq.Drive : 1/2" **Bolt Capacity** : 5/8" Max. Torque Range: 440 ft-lbs. Free Speed : 10,000 rpm Overall Length : 5-1/4" Net Weight : 2.1 lbs. Vibration Level : 5.5 m/s² Sound Level : 93.1 dB









One Hand **Reverse Button**

DR IMPACT WRENGHISS

SP-7140 (1/2") US PAT.No. D 434,958 / D 436,818

SP-7141 (1/2") US PAT.No. D 434,958 / D 436,818



VISUAL FORWARD REGULATO R WITH 4 TORQUE SETTINGS AND ONE FULL POWER IN REVERSE

VISUAL ONE-TOUCH LEVER FORWARD/ REVERSE.



Twin Dog Clutch



Sq. Drive **Bolt Capacity** Max. Torque Free Speed Overall Length

Net Weight Vibration Level Sound Level

: 5/8* : 750 ft-lbs. : 6,000 rpm : 7-5/16" 4.6 lbs.

: 3.2 m/s

: 86 dB

Sq. Drive **Bolt Capacity** Max. Torque Free Speed Overall Length Net Weight Vibration Level Sound Level

: 5/8" : 750 ft-lbs. : 6,000 rpm : 7-3/4" : 4.9 lbs. : 3 m/s2 : 85.4 dB



SOLDR. IMPACT WRENCHES.

SP-7143DX (1/2")

US PAT.No. D 434,958 / D 436,818

mini Lightweight 3lbs.

SP-7142DX (1/2") SP-7142DXS (3/8")

mini Lightweight 3lbs.

US PAT.No. D 434,958 / D 436,818







VISUAL FORWARD, REVERSE **REGULATOR WITH 4 TORQUE** SETTING.



Dyna Jaw Clutch



Sq. Drive **Bolt Capacity** Max. Torque Free Speed Overall Length Net Weight Vibration Level

Sound Level

: 1/2" : 5/8" : 425 ft-lbs. : 7,500 rpm : 6-3/4" : 3 lbs. : 3.3 m/s²

: 86dB

Sq. Drive **Bolt Capacity** Max. Torque Free Speed Overall Length Net Weight

: 3/8" : 1/2" : 425 ft-lbs. : 7,500 rpm : 6-3/4" 3 lbs. Vibration Level : 4.7 m/s² : 86 dB Sound Level

Twin Dog Clutch



4"SODR IMPACT WRENCHES





SP-7151 (3/4")




Twin Dog Clutch

: 94.9 dB

Sound Level





Vibration Level

Sound Level



5.5 m/s²

94.6 dB



SP-1158 (3/4")

Single Dog Clutch





SP-1158L (3/4")



Bolt Capacity Max. Torque Range: 1,200 ft-lbs. : 5,500 rpm Free Speed Overall Length Net Weight 12 lbs. Vibration Level : 5.62 m/s2

93.5 dB

Sound Level

SP-1158EX (3/4")



SP-1158EXL (3/4")

Net Weight

Vibration Level

Sound Level



: 14.3 lbs.

: 15.1 m/s²

: 92.8 dB



Sq.Drive **Bolt Capacity** Max. Torque Range : 1,200 ft-lbs. Free Speed 5,500 rpm Overall Length : 8-5/8" Net Weight : 12 lbs. Vibration Level : 15 m/s² Sound Level : 92.8 dB

SQ.DR. IMPACT WRENCHES

SP-7191S (1")




SP-7191 (1")







Overall Length : 10-1/2" Net Weight : 9.3 lbs. Vibration Level : 5.5 m/s2 Sound Level : 94.6 dB





Sq.Drive **Bolt Capacity** : 1-1/4" Max. Torque Range: 1,200 ft-lbs. Free Speed : 4,300 rpm Overall Length : 12-1/2" Net Weight : 10.3 lbs. Vibration Level : 5.5 m/s2 Sound Level : 90.4 dB

SP-1191DH (1")



SP-1191LDH (1")



Single Dog Clutch

Sq.Drive **Bolt Capacity** Max. Torque Range: 1,200 ft-lbs. : 5,500 rpm Free Speed Overall Length Net Weight : 13.7 lbs. Vibration Level : 5.62 m/s2 Sound Level : 92.5 dB



: 5,500 rpm Overall Length Net Weight 14.3 lbs. Vibration Level : 5 62 m/s2 Sound Level : 92.5 dB

SP-1191EXDH (1")



SP-1191EXLDH (1")



: 14.3 lbs.

: 5.62 m/s²

: 92.5 dB

Vibration Level

Sound Level

Twin Dog Clutch



Sq.Drive **Bolt Capacity** Max. Torque Range Free Speed 5,500 rpm Overall Length : 8-5/8 Net Weight : 13.7 lbs. Vibration Level : 5.62 m/s² Sound Level : 92.5 dB

1"SOLDR IMPACT WRENCHES

SP-1190PA-2 (1")



 Sq.Drive
 : 1*

 Bolt Capacity
 : 1-1/4*

 Max. Torque Range
 : 1,500 ft-lbs.

 Free Speed
 : 4,000 rpm

 Overall Length
 : 9-7/8*

 Net Weight
 : 18.9 lbs.

 Vibration Level
 : 6.3 m/s²

Sound Level



SP-1190PA-6 (1")



 Sq.Drive
 :1"

 Bolt Capacity
 :1-1/4"

 Max. Torque Range
 :1,500 ft-lbs.

 Free Speed
 :4,000 rpm

 Overall Length
 :15-3/4"

 Net Weight
 :21.2 lbs.

 Vibration Level
 :7.3 m/s²

 Sound Level
 :92 dB



SP-1190EXPA-2 (1")



 Sq.Drive
 1*

 Bolt Capacity
 1-1/4*

 Max. Torque Range
 1,500 ft-lbs.

 Free Speed
 4,000 rpm

 Overall Length
 9-7/8*

 Net Weight
 18.9 lbs.

 Vibration Level
 6.3 m/s²

 Sound Level
 92 dB



SP-1190EXPA-6 (1")



 Sq.Drive
 : 1"

 Bolt Capacity
 : 1-1/4"

 Max. Torque Range
 : 1,500 ft-lbs.

 Free Speed
 : 4,000 rpm

 Overall Length
 : 15-3/4"

 Net Weight
 : 21.2 lbs.

 Vibration Level
 : 7.3 m/s²

Sound Level



SP-1190A-2 (1")



Single Dog Clutch

SP-1190A-6 (1") **SP-1190A-8** (1")

: 92 dB



Single Dog Clutch

SP-1190EXA-2 (1")



Twin Dog Clutch

SP-1190EXA-6 (1") **SP-1190EXA-8** (1")



Twin Dog Clutch

 Sq.Drive
 :1*

 Bolt Capacity
 :1-1/4*

 Max. Torque Range
 :1,500 ft-lbs.

 Free Speed
 :4,000 rpm

 Overall Length
 :18-7/8*

 Net Weight
 :21.6 lbs.

 Vibration Level
 :5.8 m/s²

 Sound Level
 :93 dB

ODR IMPACT WRENCHES

SP-1192EX-2 (1")



: 96.5 dB



Twin Dog Clutch



Sa.Drive **Bolt Capacity** : 1-1/2" Max. Torque Range: 1,650 ft-lbs. : 4,100 rpm : 14-3/16" Free Speed Overall Length Net Weight 14.1 lbs. Vibration Level : 6.3 m/s²

Sound Level

Twin Dog Clutch

Sq.Drive **Bolt Capacity** : 1-1/2" Max. Torque Range: 1,650 ft-lbs. : 4,100 rpm Free Speed Overall Length : 20-1/8" Net Weight : 15.7 lbs. Vibration Level : 6.8 m/s² : 96.5 dB Sound Level

SP-1186GE-2 (1")



Pinless Hammer

Sq.Drive : 1-1/2" **Bolt Capacity** Max. Torque Range: 2,200 ft-lbs. Free Speed: 3,200 rpm Overall Length : 15-3/4" Net Weight : 32.4 lbs. Vibration Level : 12.5 m/s² Sound Level

SP-1186GE-8 (1")



Pinless Hammer



Bolt Capacity : 1-1/2" Max. Torque Range : 2,100 ft-lbs. Free Speed 3,200 rpm Overall Length 23-5/8" Net Weight 36.2 lbs. Vibration Level 14 m/s Sound Level

SP-5000GE (1")



Sq.Drive : 1" : 2" **Bolt Capacity** Max. Torque Range: 2,500 ft-lbs.

Free Speed : 3,000 rpm Overall Length : 25" Net Weight : 39.5 lbs. Vibration Level : 5 m/s2 Sound Level : 96 dB

"SOJDR IMPACT WRENCH

SP-6500 (1-1/2")



: 1-1/2" Sq.Drive : 2-3/16" **Bolt Capacity** Max. Torque Range: 3,000 ft-lbs. Free Speed : 3,600 rpm Overall Length : 21-3/4" Net Weight : 39.9 lbs. Vibration Level : 9.3 m/s2 Sound Level : 107 dB

Reaction Free Ratchet Wrench

SP-1764 (1/4") **SP-1765** (3/8")



U.S.Patent No.8,261,849







SP-1764

Drive Size : 1/4" **Bolt Capacity** : 5/16" Maximum Torque: 50 ft-lbs. Free Speed 500 rpm Overall Length 6-7/8" **Net Weight** 1.4 lbs. Vibration Level : 2.4 m/s² Sound Level : 83.6 dB

SP-1765

Drive Size : 3/8" **Bolt Capacity** 3/8" Maximum Torque: 55 ft-lbs. Free Speed 500 rpm : 6-7/8" Overall Length **Net Weight** : 1.4 lbs. Vibration Level : 2.9 m/s² Sound Level : 84.4 dB

Aluminum Housing

Single Dog Clutch



SP-7720A (1/4")

SP-7722A (3/8")











Built-in Power Regulator

Reaction Free Mechanism

SP-7720A

Drive Size : 1/4" **Bolt Capacity** : 5/16" Maximum Torque: 50 ft-lbs. Free Speed 500 rpm Overall Length : 6-1/8" **Net Weight** : 1.3 lbs. Vibration Level : 2.4 m/s² Sound Level : 83.6 dB

SP-7722A

Drive Size : 3/8" **Bolt Capacity** : 3/8" Maximum Torque: 55 ft-lbs. Free Speed : 500 rpm Overall Length 6-1/8" **Net Weight** : 1.3 lbs. Vibration Level 2.4 m/s² Sound Level : 83.6 dB

IMPACT RATCHET EXHIBITS FULL PERFORMANCE EVEN IN ANY RESTRICTED AREA.

(1) To tighten manually in a restricted area is difficult.



2 It is frustrating trying to work in a restricted area without hurting your hand.



The shock from a normal air ratchet can painful.

(3)



This tool is as Powerful as a small Impact Wrench.

(4)



REACTION FREE RATICETET WRENCH

SP-7730 (3/8")

RATCHEPACT U.S.Patent No.8,261,849







 Sq.Drive
 : 3/8"

 Bolt Capacity
 : 3/8"

 Max. Torque Range
 : 100 ft-lbs.

 Free Speed
 : 450 rpm

 Overall Length
 : 11-5/8"

 Net Weight
 : 3.1 lbs.

 Vibration Level
 : 5.8 m/s²

 Sound Level
 : 88.2 dB

SP-7731 (1/2")

RATCHEPACT U.S.Patent No.8,261,849







 Sq.Drive
 : 1/2"

 Bolt Capacity
 : 1/2"

 Max. Torque Range
 : 110 ft-lbs.

 Free Speed
 : 450 rpm

 Overall Length
 : 11-5/8"

 Net Weight
 : 3.1 lbs.

 Vibration Level
 : 5.8 m/s²

 Sound Level
 : 88.2 dB

Reaction Free Mecanism









SP-1175B (3/8")

RATCHEPACT U.S.Patent No.4,821,611



Pin Type Clutch

Sa.Drive : 3/8 : 1/2" **Bolt Capacity** Max. Torque Range: 90 ft-lbs. Free Speed 280 rpm Overall Length 11-1/2" Net Weight 3.1 lbs. Vibration Level : 4.5 m/s2 Sound Level : 90 dB

SP-1176B (1/2")

RATCHEPACT U.S.Patent No.4,821,611





Sa.Drive : 1/2 **Bolt Capacity** : 1/2" Max. Torque Range 95 ft-lbs. Free Speed 280 rpm Overall Length 11-1/2" Net Weight 3.1 lbs. Vibration Level : 4.5 m/s Sound Level : 91 dB

<u>1/4"&3/8"&1/2"SQDR.RATCHET WRENCHES</u>



PATENT PENDING



To adjust head push ring forward and turn.

SP-7740RH (1/4")



Sq. Drive Bolt Capacity : 5/16" Max. Torque Range: 25 ft-lbs. Free Speed Overall Length 310 rpm : 5" 1.1 lbs. Net Weight Vibration Level : 3.5 m/s2 Sound Level : 78.5 dB

SP-7742RH (3/8")

Rotational Head

super mini



Sq. Drive : 3/8" Bolt Capacity : 5/16" Max. Torque Range 25 ft-lbs. Free Speed Overall Length 310 rpm 1.1 lbs. Net Weight Vibration Level 3.5 m/s2 Sound Level : 78.5 dB

SD

SP-7770 (1/4")



Sq. Drive **Bolt Capacity** :5/16" Max. Torque Range: 25 ft-lbs. Free Speed : 220 rpm Overall Length : 7-7/8" Net Weight : 1.3 lbs. Vibration Level : 3.5 m/s2 Sound Level

SP-7772 (3/8") mini



Sq. Drive **Bolt Capacity** : 3/8" · 25 ft-lbs Max. Torque Range Free Speed 220 rpm Overall Length Net Weight : 1.3 lbs. Vibration Level : 3.5 m/s2

Sound Level : 82 dB

SP-7130RH (3/8")



: 3/8" **Bolt Capacity** Max. Torque Range: 90 ft-lbs. Free Speed : 180 rpm Overall Length : 10-5/8" Net Weight · 29 lbs Vibration Level : 3.3 m/s² Sound Level

SP-7131RH (1/2")



Sq. Drive Bolt Capacity : 1/2" : 3/8" Max. Torque Range 90 ft-lbs. Free Speed 180 rpm Overall Length 10-5/8" Net Weight 29 lbs Vibration Level : 3.3 m/s² Sound Level :84 dB

1/4"&3/8"&1/2"SQDR RATCHET WRENCHES

SP-1760A (1/4")

mini



\$q.Drive : 1/4"
Bolt Capacity : 5/16"
Max. Torque Range : 25 ft-lbs. Free Speed : 310 rpm
Overall Length : 6-5/8"
Net Weight : 1.1 lbs.
Vibration Level : 3.5 m/s²
Sound Level : 84 dB

SP-1762 (3/8")

mini



 Sq.Drive
 3/8"

 Bolt Capacity
 3/8"

 Max. Torque Range
 25 ft-lbs.

 Free Speed
 310 rpm

 Overall Length
 6-5/8"

 Net Weight
 1.1 lbs.

 Vibration Level
 3.5 m/s²

 Sound Level
 83 dB

SP-7760 (1/4")

mini

US PAT.No. D 408,243 6,158,528



Sq. Drive : 1/4"
Bolt Capacity : 5/16"
Max. Torque Range : 25 ft-lbs.
Free Speed : 220 rpm
Overall Length : 7-7/8"
Net Weight : 1.3 lbs.
Vibration Level : 3.5 m/s²
Sound Level : 82 dB

SP-7762 (3/8")

mini

US PAT.No. D 408,243 6,158,528



 Sq. Drive
 : 3/8"

 Bolt Capacity
 : 3/8"

 Max. Torque Range
 : 25 ft-lbs.

 Free Speed
 : 220 rpm

 Overall Length
 : 7-7/8"

 Net Weight
 : 1.3 lbs.

 Vibration Level
 : 3.5 m/s²

 Sound Level
 : 82 dB

SP-1133 (3/8")



SP-1133-2 (1/2")



 Sq.Drive
 : 1/2"

 Bolt Capacity
 : 3/8"

 Max. Torque Range
 : 55 ft-lbs.

 Free Speed
 : 160 rpm

 Overall Length
 : 10"

 Net Weight
 : 2.6 lbs.

 Vibration Level
 : 3.5 m/s²

 Sound Level
 : 91 dB

SP-7130 (3/8")

Sq. Drive : 3/8" Bolt Capacity : 3/8"

Bolt Capacity : 3/8"
Max. Torque Range : 90 ft-lbs.
Free Speed : 180 rpm
Overall Length : 10-5/8"
Net Weight : 2.9 lbs.
Vibration Level : 3.3 m/s²
Sound Level : 84 dB

SP-7131 (1/2")



Sq. Drive : 1/2"
Bolt Capacity : 3/8"
Max. Torque Range : 90 ft-lbs.
Free Speed : 180 rpm
Overall Length : 10-5/8"
Net Weight : 2.9 lbs.
Vibration Level : 3.3 m/s²
Sound Level : 84 dB

DIE GRINDERS

SP-7240H super mini

SP-7241H super mini





Mini Body Size

Only 66mm Short Body







Collet Size : 1/4"
Free Speed : 16,000 rpm
Overall Length : 4-5/8"
Net Weight : 1 lbs.
Vibration Level : 1.6 m/s²
Sound Pressure Level : 83.3 dB

SP-7211

SP-7220





Collet Size : 1/4"
Free Speed : 18,000 rpm
Overall Length : 6-7/8"
Net Weight : 1.75 lbs.
Vibration Level : 1.5 m/s²
Sound Level : 87.8 dB

Collet Size : 1/4"
Free Speed : 20,000 rpm
Overall Length : 6-7/8"
Net Weight : 1.37 lbs.
Vibration Level : 7.3 m/s²
Sound Level : 90.1 dB

SP-7230 Cut-Off Tool



Disc Size : 3"
Free Speed : 20,000 rpm
Overall Length : 6-3/4"
Net Weight : 1.5 lbs.
Vibration Level : 1.9 m/s²
Sound Level : 90 dB

DIE GRINDERS

SP-7200



D 408,243 6,158,528

Collet Size : 1/4"
Free Speed : 23,000 rpm
Overall Length : 6"
Net Weight : 0.9 lbs.
Vibration Level : 2 m/s²
Sound Level : 82 dB

SP-7201



Collet Size : 1/4"
Free Speed : 20,000 rpm
Overall Length : 6-3/8"
Net Weight : 1.2 lbs.
Vibration Level : 2.8 m/s²
Sound Level : 82.4 dB

SP-7202



Collet Size : 1/4"
Free Speed : 20,000 rpm
Overall Length : 7-5/8"
Net Weight : 1.2 lbs.
Vibration Level : 2.8 m/s²
Sound Level : 83 dB

SP-1220S (1/4")



Collet Size : 1/4"
Free Speed : 23,000 rpm
Overall Length : 6-1/2"
Net Weight : 1.2 lbs.
Vibration Level : 1.4 m/s²
Sound Level : 87 dB

SP-1523S (1/4")



Collet Size : 1/4"
Free Speed : 3,800 rpm
Overall Length : 7-1/2"
Net Weight : 1.6 lbs.
Vibration Level : 0.35 m/s²
Sound Level : 87 dB

DISC GRINDERS

SP-1254



SPINDLE

Disc Cap : 4"
Free Speed : 12,000 rpm
Overall Length : 9"
Net Weight : 3.7 lbs.
Vibration Level : 1.2 m/s²
Sound Level : 89 dB

SP-1257



SPINDLE M14×2

Disc Cap : 5"
Free Speed : 12,000 rpm
Overall Length : 9"
Net Weight : 3.7 lbs.
Vibration Level : 1.5 m/s²
Sound Level : 86 dB

SP-1261L14



SPINDLE M14×2

 Disc Cap
 : 7"

 Free Speed
 : 7,500 rpm

 Overall Length
 : 12-5/8"

 Net Weight
 : 7.7 lbs.

 Vibration Level
 : 1.2 m/s²

 Sound Level
 : 86 dB

SP-7520KL 3/8" COMPOSITE AIR DRILL





SPECIFICATIONS

CHUCK SIZE : 3/8"
FREE SPEED : 500 rpm
OVERALL LENGTH : 6-1/8"
WEIGHT : 2.3 lbs.
VIBRATION LEVEL : 0.17 m/s²
SOUND LEVEL : 88.0 dB
AIR INLET : 1/4"NPT

<u> 31/2" KEYLESS DRILLS.</u>

SP-7525KL (3/8")

Lightweight Composite Body



SP-7527KL (1/2")

Lightweight Composite Body











Chuck Size : 3/8" Free Speed : 2,000 rpm Overall Length: 6-1/8" Net Weight : 2.1 lbs. Vibration Level : 0.26 m/s² Sound Level : 87 dB



Reversible Type

Chuck Size : 1/2" Free Speed 400 rpm Overall Length: 7" Net Weight : 2.9 lbs. Vibration Level : 0.14 m/s²



• Reversible Type

SP-1523KL (3/8")



Chuck Size . 3/8" Free Speed : 3,800 rpm Overall Length: 7-1/2" Net Weight : 1.6 lbs. Vibration Level: 0.35 m/s2 : 83 dB Sound Level



Oneway Type

SP-1522KL (3/8")

• W/ SILENCER

Sound Level



Chuck Size : 3/8" Free Speed : 2,500 rpm Overall Length : 6-3/4" Net Weight : 2.1 lbs. Vibration Level : 0.4 m/s2 Sound Level : 84 dB

SP-1510AH-KL (3/8")



Chuck Size

Free Speed

Sound Level

Overall Length Net Weight



• Reversible Type

SP-1525KL (3/8")



Chuck Size : 3/8" Free Speed : 2,200 rpm Overall Length: 7-5/8" Net Weight : 2.7 lbs. Vibration Level : 0.35 m/s Sound Level

Reversible Type

SP-1527KL (1/2")

: 8-5/8"

: 89 dB



W/SILENCER

SP-1533KL (1/2")



Chuck Size : 550 rpm Free Speed Overall Length: 8-3/4" Net Weight 3.5 lbs. Vibration Level : 0.4 m/s² Sound Level : 84 dB

AIR VERTICAL BEVELER

PSPC STANDARDS
(Performance Standard for Protective Coating)

SP-1251LABV




PATIENTED

3 Bladed Cutting Head




Patented 8 Edged Cutters




Machines chamfering capabilities

Cuts inside circles with a 1-3/8" diameter or more

Cuts materials with a minimum of 1/4" thickness



Will make blind cuts with a minimum of 7/16" depth



//A.SANDERS

SP-3606-A5 (6")



Pad Size Orbit Dia. : 3/16" : 10,000 rpm Free Speed Overall Length: 8-1/2" Net Weight 2.7 lbs. Vibration Level : 2.5 m/s² Sound Level : 90 dB



Dust Free Type



Pad Size Orbit Dia. : 3/16" : 10,000 rpm Free Speed Overall Length: 9-1/2" Net Weight : 2.8 lbs. Vibration Level : 2.5 m/s² Sound Level : 85 dB



BHIT SANDHRS.





ANDERS & POUSERS

SP-7241GH (2")

Single Action

super mini

Sound Level : 82 dB














Net Weight : 1 lbs. Vibration Level : 0.16 m/s² Sound Level : 78.3 dB

SP-7500AH-P (5")



Pad Size : 5/16-24 UNF Spindle Size : 2,000 rpm Free Speed Overall Length: 8" Net Weight : 2.6 lbs. Vibration Level: 0.34 m/s2 Sound Level : 83.2 dB





SP-7201G (2")

Single Action

mini







Spindle Size Free Speed : 14,000 rpm Overall Length: 6-1/4" Net Weight : 1.2 lbs. Vibration Level : 0.34 m/s² Sound Level : 83.2 dB

SP-1350 (4")



: 3" : 15,000 rpm Overall Length Net Weight : 2.1 lbs. Vibration Level 4 5 m/s Sound Pressure Level: 77.8 dB

SCREW DRIVIERS

SP-1800A

External Adjustment Type



Hex. Drive : 1/4" **Bolt Capacity** Overall Length Net Weight : 2.8 lbs. Vibration Level : 0.8 m/s2 Sound Level : 85 dB

ADJUSTABLE KNOB



SP-1810A

External Adjustment Type




SP-1800

Internal Adjustment Type



Hex. Drive : 1/4" **Bolt Capacity** Overall Length :10" Net Weight : 2.4 lbs. Vibration Level : 0.8 m/s2 :81 dB Sound Level





SP-1810

Internal Adjustment Type



MPACT DRIVIERS

SP-7825HU

Lightweight Composite Body



Clutch

Hex. Drive

Net Weight

Sound Level

: 1/4"

: 1.5 lbs.

: 85.5 dB

Max. Torque : 94 ft-lbs. Overall Length : 4-1/2"

Vibration Level : 3.5 m/s2



Air Regulator

One Hand **Reverse Button**



SP-8102BU



Clutch

Sound Level




Hex. Drive Max. Torque : 100 ft-lbs. Overall Length : 6" Net Weight Vibration Level : 2.6 lbs. : 3.9 m/s²

: 90 dB

















Cutting Capacity : 1/32"
Free Speed : 3,400 rpm
Stroke : 3/16"
Overall Length : 8-3/4"
Net Weight : 1 lbs.
Vibration Level : 3.6 m/s²
Sound Level : 80 dB

OPTION BLADES #7600-03 32T-Steel





SP-1720



Cutting Capacity : 1/16"
Free Speed : 11,000 rpm
Overall Length : 1*
Net Weight : 1.1 lbs.
Vibration Level : 92 dB

OPTION BLADES
#720-70
32T-Steel
#720-71
24T-Steel

FAMMERS

SP-1410

SP-1410H

Hexagonal Type



opm

SP-1410K (BOX SET)



Low Wibration Long Flux Chipper Strain!

FLUX CHIPPER

SP-1490L

LOW VIBRATION LONG FLUX CHIPPER

Vibration is 10 times lower than other current models.

with less strain on the users back and legs.

Tool is most suitable for tile stripping and rust removal.

New long design makes it easier to use

Both lever and rotary grip types are available.

To see the SP-1490L in operation go to http://www.spair.co.jp/







■ □ ■ SPECIFICATIONS ■ □ ■

Outside Dia. : 3-1/2"
Piston : 1"
Piston Stroke : 7/8"

Blows Per Min. : 4,600bpm

Overall Length : 63"

Weight : 28.2 lbs. Hose Size : 3/8" Air Inlet : PT1/4"

Air Consumption: 8.5 cfm Air Pressure 58 PSI

NEEDLE SCALERS & FLUX CHIPPERS

SP-1460

NEEDIES GAVER



Model No.	Piston Dia.	Piston Stroke	Needles to be used	Blows / min.	Overall Length	Weight	Air Consumption	Air Inlet
SP-1460	3/4"	1/2"	OD 3×7" (12pcs.)	5,000 bpm	9"	2.8 lbs.	5.3 cfm	1/4"

SP-1470

NEEDLE SOMER



Model No.	Piston Dia.	Piston Stroke	Needles to be used	Blows / min.	Overall Length	Weight	Air Consumption	Air Inlet
SP-1470	1"	7/8"	OD 3×7" (19pcs.)	4,000 bpm	16"	5.7 lbs.	14.3 cfm	1/4"

SP-1460FC

FLUX CHIPPER



Model No.	Piston Dia.	Piston Stroke	Blows / min.	Overall Length	Weight	Air Consumption	Air Inlet
SP-1460FC	3/4"	1/2"	5,000 bpm	7"	2 lbs.	5.3 cfm	1/4"

SP-1470FC

FLUX CHIPPER



Model No.	Piston Dia.	Piston Stroke	Blows / min.	Overall Length	Weight	Air Consumption	Air Inlet
SP-1470FC	1"	7/8"	4,000 bpm	9"	3.7 lbs.	14.3 cfm	1/4"

1" SQ.DR. IMPRCT WRENCHES

SP-1193GE-8 1" SQ.DR.



AIR REGULATOR (STRAIGHT TYPE)

SP-1193G€-8

: 1" Sq.Drive

Bolt Capacity : 1-5/8"

Max. Torque : 2,300 ft-lbs. Free Speed : 4,000 rpm

Ovarall Length : 24"

Net Weight : 28.7 lbs.



SP-1193GEP 1" SQ.DR.



2" SHORT ANVIL





SP-1193GEP-2 (SHORT ANVIL)

: 1" Sq.Drive

Bolt Capacity : 1-5/8"

Max. Torque : 2,300 ft-lbs. Free Speed : 4,000 rpm

Ovarall Length: 11"


: 23 lbs. Net Weight

<u>AVNYIILIKIIIS FOR RATIGIIBT WYRIANGII.</u>



Tool No.	Anvil Kit No.		
SP-7760(1/4")	AK-7760		
SP-7770(1/4")	AK-7700		
SP-1760A(1/4")	AK-760		
SP-7740RH(1/4")	AK-700		
SP-7762(3/8")	AK-7762		
SP-7772(3/8")	AK-7702		
SP-1762(3/8")	AK-762		
SP-7742RH(3/8")	AK-702		
SP-1133(1/2")			
SP-1134(1/2")	AK-131		
SP-7131(1/2")	AK-131		
SP-7131RH(1/2")			
SP-1133(3/8")			
SP-1134(3/8")	AK-130		
SP-7130(3/8")	AK-130		
SP-7130RH(3/8")			

OSTANTO COUPLING ASSTAMBLY



- SP AIR tools precision products built to perform in a wide variety application. Peak performance can be assured by following a few simple guidelines.
- Always use 0.63 MPa (6.3 bar/90 PSI) air pressure at the tool. Exceeding 0.63 MPa (6.3 bar/90 PSI) will result in premature wear an possible breakage.
- Lubricate your tool daily. An inline lubricator is recommend. Daily lubrication will prevent excessive wear or moving parts, rust and corrosion of bare metalsurfaces and assures peak performance of the tool. Tools requiring grease should be checked at regular intervals.
- Keep your air system clean and dry. Drain your system daily. Water increases the risk of rusted parts and premature wear.
- Always wear safety goggles!
 Operating your air tool without oil and with more than 0.63 MPa (6.3 bar/90 PSI) is like driving your car without oil past the red line.



http://www.spair.co.jp/

DISTRIBUTED BY: